



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Decal & Paint Stripper

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Decal & Paint Stripper is a solvent stripper specifically designed to quickly remove decals, stickers and paint from bumpers and truck bodies. Works in 15 minutes at temperatures from 40°F to 100°F (5°C to 38°C).

CAUTION: This product will remove paint. Do not use to remove decals from painted surfaces.

PRODUCT BENEFITS

- Eliminates time consuming scraping and sanding
- Adheres to vertical surfaces

TYPICAL APPLICATIONS

Removes decals, bumper stickers or paint from:

- Auto bodies
- Bumpers
- Windows
- Windshields

DIRECTIONS FOR USE

1. Provide adequate ventilation and protect painted surfaces.
2. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
3. Hold the can 8 to 10 inches from the surface to be stripped. Press the nozzle and discharge and saturate the product liberally on the area to be removed.
4. Allow 5 to 10 minutes for product to penetrate. Then lift the decal with a putty knife.

For Cleanup

1. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Chlorinated solvent
Appearance	Milky liquid
Odor	Mild
Flash Point	Aerosol, contents under pressure, consult MSDS
NFPA 704 Flammability Rating	4 (Highly flammable)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80577 (161DA)	16 oz. aerosol can

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.