



Toll Free: 87 PERMATEx
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Flowable Silicone Windshield and Glass Sealer

INDUSTRIAL

PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Flowable Silicone Windshield and Glass Sealer is a solventless, flowable silicone RTV designed to flow into cracks and seams to form a clear, tough flexible seal. It flows into hidden and hard-to-reach areas. It cures to a tough waterproof, durable, clear seal that is resistant to weather, extreme temperatures, vibration, shock and most shop chemicals.

PRODUCT BENEFITS

- Easy to use
- Flowable
- Temperature range -80°F to 450°F (-62°C to +232°C)
- Waterproof

TYPICAL APPLICATIONS

- Windshields
- Sunroofs
- Windows
- Headlamp assemblies
- Marine glass
- RV vents and windows

DIRECTIONS FOR USE

1. Locate source of leak.
2. Clean and dry surfaces with alcohol.
3. Apply Permatex® Flowable Silicone Windshield and Glass Sealer into the leak source; allow time for penetration.
4. Wipe off excess sealant with clean rag.
5. Sealant is tack-free in one hour. Full cure within 24 hours.

PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Polysiloxane
Appearance	Clear
Specific Gravity	1.05
Viscosity	Flow is similar to syrup
Flash Point, TCC, °C (°F)	> 93 (200)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
81730 (65AR)	1.5 fl. oz. tube, carded

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8_ to 28_C (46_ to 82_F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEx, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEx, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87)PERMATEx Revised 09/02