



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# Permatex® Super Glue Adhesive

INDUSTRIAL

### PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Super Glue is an instant-bonding adhesive designed to bond close fitting surfaces quickly. Sets in seconds to form a permanent, transparent bond. Effective on metal, rubber, glass, aluminum, ceramics, vinyl, alloys, plastics and other non-porous surfaces.

### PRODUCT BENEFITS

- Ready to use
- No mixing
- Permanent, transparent bond
- Fills gaps to .004"

### TYPICAL APPLICATIONS

- Bonds rubber, plastic and metal

### DIRECTIONS FOR USE

1. Protect the work surface against accidental spills, as cyanoacrylates can mark finishes and fabrics.
2. Clean and ensure a close fit on the surfaces to be bonded. Wiping wood with a damp cloth will increase bonding speed.
3. To use the clean and easy self-piercing tube, screw nozzle onto tube clockwise, hold base of nozzle and remove the cap counter-clockwise.
4. Apply the glue to one of the surfaces. Use sparingly, one square inch of surface area requires only one drop of glue.
5. Hold the surfaces to be bonded together for 15 to 30 seconds. No clamping is required, even on wood. **DO NOT REPOSITION THE PARTS.**
6. Replace the cap, and store the glue in a cool spot.
7. Allow the parts to cure overnight.

### For Cleanup

1. To remove Super Glue, use Super Glue Remover, acetone or nail polish remover that contains acetone.
2. To remove from hard surfaces such as Formica®, saturate a soft cloth or paper towel with the acetone and allow to rest on the spot for about 10 – 15 minutes. After the Super Glue is removed, a white or light colored spot may be left which is easily removed by applying mineral oil to the spot to restore the color.
3. Clean hands with Super Glue Remover or acetone then use Permatex® brand hand cleaners.

### PROPERTIES OF UNCURED MATERIAL

	Typical Value
Chemical Type	Ethyl cyanoacrylate
Appearance	Colorless liquid
Odor	Mild Pungent
Specific Gravity	1.06
Viscosity, Brookfield LVF, Spindle 1, 30rpm, 25C, cP	20 - 60
Flash Point, TCC, °F	> 200

### TYPICAL CURING PERFORMANCE

Permatex® Super Glue cures on exposure to moisture. Fixture time is 15 – 30 seconds and full cure within 2 hours. - Cured temperature range °F (°C) - -65 to +180(-53 to +82)

### GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

### ORDERING INFORMATION

Part Number	Container Size
82190	2 g tube, 1-pack carded
30878	2 g tube, 2-pack carded

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° to 28°C (46° to 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.